



Enhanced Real-Time Charging Station Recommendation System for Load Base Electric-Vehicle Taxis

¹P.Pavithra, ²B.Yeshwanth, ³M.Parvathi, ⁴E.Padma,
^{1,2} PG Scholars, ^{3,4} Associate Professor

Department of Computer Science and Engineering
Nandha Engineering College(Autonomous),Erode.

paviperumal73@gmail.com, yeshwanth104@gmail.com, padma.e@nandhaengg.org, mparvathicse@gmail.com

Abstract— Electric Vehicles (EV) have limited air pollution and are many environment friendly, and due to their addition to carbon dioxide reduction, EVs are enhancing increasingly popular nowadays. The government also encourage and supporting the procedure of electric vehicles for the social. The electric vehicle - taxis have been discovered into the common transportation systems to increase EV market distribution. Various from regular taxis that can refuel in minutes, EV taxis' recharging cycles can be as lengthy as one hour. Due to the lengthy cycle, the poor decision on the charging station, i.e., choosing one without hollow charging piles, may lead to a lengthy waiting time of more than an hour in the bad case. Therefore, choosing the right charging station is very necessary to reduce the overall waiting time. Considering that the waiting time can be a non negligible portion to the mistken work hours, the decision will naturally distrub the revenue of individual EV taxis. The current practice of a taxi driver is to choose a station heuristically without a global knowledge. However the heuristically choice can be a wrong one that leads to more waiting time. The proposed system provides a real-time charging station recommendation system for EV taxis via large-scale GPS text mining. By combining each EV taxi's historical recharging events and real-time GPS trajectories, the data operational state of each taxi is predicted. Based on this data, for an EV taxi requesting a recommendation, recommend a charging station that

leads to the minimal total time previous its recharging starts.

Keywords-Index Terms—*Electric vehicle (EV), charging station, recommendation,taxis*

1. INTRODUCTION

Data mining, or knowledge discovery, is the computer-assisted process of digging through and analyzing enormous sets of data and then extracting the meaning of the data. Data mining tools predict behaviors and future trends, allowing businesses to make proactive, knowledge-driven decisions. Data mining tools can answer business questions that traditionally were too time consuming to resolve. They scour databases for hidden patterns, finding predictive information that experts may miss because it lies outside their expectations. Data mining derives its name from the similarities between searching for valuable information in a large database and mining a mountain for a vein of valuable ore. Both processes require either sifting through an immense amount of material, or intelligently probing it to find where the value resides.

Although data mining is still in its infancy, companies in a wide range of industries - including retail, finance, health care, manufacturing transportation, and aerospace - are already using data mining tools and techniques to take advantage of historical data. By using pattern recognition technologies and statistical and

mathematical techniques to sift through warehoused information, data mining helps analysts recognize significant facts, relationships, trends, patterns, exceptions and anomalies that might otherwise go unnoticed. For businesses, data mining is used to discover patterns and relationships in the data in order to help make better business decisions. Data mining can help spot sales trends, develop smarter marketing campaigns, and accurately predict customer loyalty.

2. RELATED WORKS

Zhiyong Tian, Yi Wang, Chen Tian, Fan Zhang, Lai Tu, Chengzhong Xu describe major obstacle to the wide acceptance of Electric Vehicles (EV) is the lack of a wide spread charging infrastructure. To solve this, the Chinese government has promoted EVs in public transportation. The operational patterns of EV taxis should be different from Internal Combustion Engine Vehicles (ICEV) taxis: EVs can only travel a limited distance due to the limited capacity of the batteries and an EV taxi may re-charge several times throughout a day. Understanding the status (e.g., operational patterns, driver income and charging behaviors) of EV taxis can provide invaluable information to policy makers. The main contributions of this paper include: 1) Overall, the travel and occupied time/distance are comparable between EV and ICEV taxis. They derive the net profits of both EV and ICEV taxis, and found that an EV taxi can earn almost as much as an ICEV taxi although the EV taxi spend more time on charging. The implication is that commercial operation of an EV taxi fleet can be profitable in metropolitan area, when specific policies give advantages to EV taxis [1].

Zhongjing Ma Duncan Callaway Ian Hiskens developed a novel decentralized charging control strategy for large populations of plug-in electric vehicles (PEVs). They consider the situation where PEV agents are rational and weakly coupled via their operation costs. At an established Nash equilibrium, each of the PEV agents reacts optimally with respect to the average charging strategy of all the PEV agents. Each of the average charging strategies can be approximated by an infinite population limit which is the solution of a fixed

point problem. The control objective is to minimize electricity generation costs by establishing a PEV charging schedule that fills the overnight demand valley. They showed that under certain mild conditions, there exists a unique Nash equilibrium that almost satisfies that goal. Moreover, the paper establishes a sufficient condition under which the system converges to the unique Nash equilibrium. The theoretical results are illustrated through various numerical examples [2].

Lingwen Gan Ufuk Topcu Steven Low proposed decentralized algorithms for optimally scheduling electric vehicle (EV) charging. The algorithms exploit the elasticity and controllability of electric vehicle loads in order to fill the valleys in electric demand profiles. They first formulate a global optimization problem, whose objective is to impose a generalized notion of valley-filling, and study the properties of optimal charging profiles. Then they give two decentralized algorithms, one synchronous (i.e., information update takes place in each iteration) and one asynchronous (i.e., EVs may use outdated information with bounded delay in some of the iterations) to solve the problem [3].

Hua Qinand Wensheng Zhang proposes a method to estimate the probability in which each reservation will be really carried out (called success probability of the reservation hereafter), and use the reservation information according to its success probability. The success probability is estimated based on the following ideas: When a reservation is made, the stability (i.e., the chance that it will not be changed or cancelled) is firstly estimated through comparing the waiting time caused by this reservation with the waiting time caused by other optional reservations. The larger is the difference, the higher is the stability. Furthermore, the historical data is used to model the mapping between the stability of reservations and the success probabilities. With the mapping, the success probability of a reservation can then be quantified based on both stability and the mapping between stability and success probability [4].

Francesco Malandrino, Claudio Casetti, Carla-Fabiana Chiasserini investigates how equilibrium in

such a market can be reached. They also address the issue of computational complexity, showing that, through their model, equilibria can be found in polynomial time. They evaluated their model in a realistic scenario, focusing on its ability to capture the advantages of the availability of an Intelligent Transportation System (ITS) supporting the EV drivers. The model also mimics the anticompetitive behavior that charging stations are likely to follow, and it highlights the effect of possible countermeasures to such a behavior. It is now an established tenet of transportation technology that Electric Vehicles (EVs) will, at some point in the future, replace vehicles propelled by fossil fuel. Environmentally friendly by definition, EVs enjoy favorable attention by industry and governments alike [5].

3. DATA PREPROCESSING AND BEHAVIOR ANALYSIS

A. EV Taxi Specifications & Charging Station Deployment

The specifications of the EV taxis in Shenzhen indicate that the distance which is fully charged EV can travel is shorter than that of a fully fueled ICEV (according to the fuel economy and the tank capacity specifications of the ICVE taxis in Shenzhen, a fully fueled ICVE can travel approximately 600 km). Meanwhile, the distribution of deployed charging stations for public Evs. There are two kinds of charging stations deployed in Shenzhen. A majority of the stations are exclusively for EVtaxis while a few are shared by EV taxis and electric buses. Neither type of stations are open for private cars. Since electric buses usually have fixed schedule and recharge at a certain fixed time at late night, the available charging stations and piles for EV taxis can be considered as static resource. They will be negligibly affected by other type of electric vehicles. Although the charging stations are mostly only for EV taxis, they are still in severe shortage to supply all EV taxis. Both above battery specifications and the current charging station deployment can lead to EV drivers' long time cost for recharging and can be obstacles in promoting the usage of EV. Infrastructure

constructions and battery technology improvement can be an option. However, the initial cost of additional infrastructure is considerably large and the construction may also be limited by some constrains such as land use and power grid. The battery technology also needs further breakthrough to be widely applied in EVs. Therefore, the status quo of the EV specifications and charging station deployment raise the emergency of an efficient charging recommendation solution



Figure:2 Distribution of charge station

B. Real-time recommendation system

It performs the EV taxi state inference, focusing on recharging intention formulation. Specifically, it investigates EV taxi drivers' recharging intentions from two perspectives:

- At a time t , how to identify whether an EV taxi v has a recharging intention.
- If v has a recharging intention, which charging station it chooses to go.

Thereafter, we will combine EV taxi drivers' recharging intentions and the occupancy of charging piles in each station to calculate waiting time at each charging station. Finally, based on the calculated waiting time, we propose a model for our real-time recommendation system. Therefore, charging stations where cost time is minimal can be recommended for EV taxi drivers who use the system, improving their operational time on roads.

C. Recharging Intention Identification

There is another factor that may influence EV taxi drivers' recharge intentions: the travel distance after the last recharging event. This can be computed by analyzing the sum of Cruise distance and Distance between two consecutive recharge events in the taxi transaction data set. Although we mainly focus on time slots when predicting states of EV taxis, it follows from our observation that an EV taxi driver do not drive to a charging station for recharging if he did not travel a long distance after the last recharging event. Thus we take this distance data set into consideration when predicting their states to avoid the occurrence of this exception.

D. Charging Station Selection

After identifying whether an EV taxi v has a recharging intention at t , we should also predict which charging station v is most probably heading to. Specifically, for v we firstly obtain a list of charging stations v choose to recharge and rank those charging stations by the frequency v has visited. It denotes v 's ordered list as $sta=(s_1,s_2,\dots,s_m)$ where s_i refers to a charging station. This ordered list reveals an EV taxi drivers preference to different charging stations and for every $s_i \in sta$, we denote c_i as the count that s_i has been visited by v for recharging.

Besides the preference to charging stations, we should also consider v 's position at t since the investigations through EV taxi drivers indicate that the drivers always prefer to drive to nearby charging stations instead of remote ones, thus for every $s_i \in sta$, we denote $dist(pm,s_i)$ as the distance between v 's current location at t and charging station s_i , where pm comes from tr_j and indicates v 's location at the moment closest to t . Then for every $s_i \in sta$, we give it a score computed as $score_i = c_i / dist(pm,s_i)$ Then we choose the charging station with the highest score as the EV taxi's station selection.

Taxi GPS traces can be exploited to investigate EV taxi drivers' recharging behavior patterns. In this paper, we have studied EV taxi drivers' recharging intention identification based on the activities of over 800 EV taxis in Shenzhen. To understand recharging intentions

of EV taxi drivers, we first propose a method to detect their recharging events and then analyze their historical recharging behavior patterns by utilizing the detected recharging events data and field investigations through EV taxis drivers. The investigations are mainly focused on two perspectives: 1) EV taxi drivers usually have recharging intentions at a fixed period; 2) although over 50 charging stations are deployed in Shenzhen, most of EV taxi drivers choose 6–8 stations among them regularly. Based on our verifications for these investigations, we combine historical recharging event data and real-time taxi GPS data to identify drivers' recharging intentions, including when and where they will choose for recharging.

In this paper, we present a real-time recommendation system for them by linking charging stations' operational condition information to reduce their cost time for recharging. The system first predicts EV taxi drivers' recharging intentions. Then, given the current location and time of an EV taxi that sending a recharging request, the system can recommend a charging station for the EV taxi driver, to which the driver's overall cost time for recharging is most likely to be minimal. Our extensive analysis on the real data set shows that our system can reduce the cost time by 50% in Shenzhen. Although the research is based on the study case in Shenzhen, we claim that most of our preliminary observations will be commonly observable among EV taxi drivers in general, and the theoretic model of our system is irrelevant to the city, which make it evident that our system is universally applicable in any city or country considering the adoption of EV taxi system.

4. CONCLUSION

In this paper, we present a real-time recommendation system for them by linking charging stations' operational condition information to reduce their cost time for recharging. The system first predicts EV taxi drivers' recharging intentions. Then, given the current location and time of an EV taxi that sending a

recharging request, the system can recommend a charging station for the EV taxi driver, to which the driver's overall cost time for recharging is most likely to be minimal. Our extensive analysis on the real data set shows that our system can reduce the cost time by 50% in Shenzhen. Although the research is based on the study case in Shenzhen, we claim that most of our preliminary observations will be commonly observable among EV taxi drivers in general, and the theoretic model of our system is irrelevant to the city, which make it evident that our system is universally applicable in any city or country considering the adoption of EV taxi system.

REFERENCES

- [1]Z. Tian et al., "Understanding operational and charging patterns of electric vehicle taxis using GPS records," in Proc. IEEE 17th Int. Conf. ITSC, 2014, pp. 2472–2479.
- [2]Z. Ma, D. Callaway, and I. Hiskens, "Decentralized charging control for large populations of plug-in electric vehicles," in Proc. 49th IEEE CDC, 2010, pp. 206–212.
- [3]L. Gan, U. Topcu, and S. Low, "Optimal decentralized protocol for electric vehicle charging," in Proc. IEEE 50th CDC-ECC, 2011, pp. 5798–5804.
- [4]R. Freire and et al., "Integration of Renewable Energy Generation with EV Charging Strategies to Optimize Grid Load Balancing". Conference on Intelligent Transportation Systems, 2010
- [5]F. Malandrino, C. Casetti, and C.-F. Chiasserini, "A holistic view of its-enhanced charging markets," IEEE Trans. Intell. Transp. Syst., vol. 16, no. 4, pp. 1736–1745, Aug. 2014.
- [6]J.Zhao, C. Tian, F. Zhang, C. Xu, and S. Feng, "Understanding temporal and spatial travel patterns of individual passengers by mining smart card data," in Proc. IEEE 17th Int. Conf. ITSC, 2014, pp. 2991–2997
- [7]F. Zhang, D. Wilkie, Y. Zheng, and X. Xie, "Sensing the pulse of urban refueling behavior," in Proc. ACM Int. Joint Conf. Pervasive UbiquitousComput., 2013, pp. 13–22
- [8]C. Chen et al., "Real-time detection of anomalous taxi trajectories from GPS traces," in Mobile and Ubiquitous Systems: Computing, Networking, and Services. New York, NY, USA: Springer-Verlag, 2012, pp. 63–74
- [9]F. Zhang et al., "Spatio-temporal segmentation of metro trips using smart card data," IEEE Trans. Veh. Technol., to be published.
- [10]D. Zhang et al., "Understanding taxi service strategies from taxi GPS traces," IEEE Trans. Intell. Transp. Syst., vol. 16, no. 1, pp. 123–135, Feb. 2015