



International Journal of Intellectual Advancements and Research in Engineering Computations

Salient Region Detection for Video Surveillance

Mrs.K.Kavitha¹, N.Keerthana², E.Monisha², R.Ragavi², R.Sowmya²

¹Assistant Professor, Department of Computer Science and Engineering, Nandha Engineering College

²UG Students Department of Computer Science and Engineering, Nandha Engineering College

ABSTRACT

The paper shows an effective and solid way to deal with programmed individuals division, following and checking, utilized in observation frameworks. Upon the underlying novel foundation extraction calculation utilizes an improved mode algorithm to get the areas of static background and novel fluffy foundation subtraction approach locales for foundation subtraction. We additionally build up a total system to assess another edge stream vector based division forms. Following divided individuals is a dynamic group task issue between two back to back casings, and it is illumi006Eated by a fluffy based guideline framework for following and individuals tallying and is connected to individuals observation. Exploratory outcomes recommend that the proposed technique can accomplish great outcomes in both checking precision and execution speed.

Index Terms: People counting, People Segmentation, Mode Background extraction, Background Subtraction, People tracking

INTRODUCTION

Effective and dependable programmed individuals recognition, following and tallying is helpful for some business applications. Individuals observation at certain open spots, including underground stations, railroad stations and open structures, depend on such frameworks, with imperative human security suggestions. While improving security, data acquired from such frameworks can likewise distinguish hourly traffic designs, enhance work planning, and screen the viability of limited time occasions. As this present reality is mind boggling, a moving target is regularly subject to foundation subtraction, occlusion and dynamic changes in light.

Foundation subtraction strategies for the most part distinguish movement in some constant vision reconnaissance applications. These methodologies consider contrasts between the approaching and foundation pictures to distinguish closer view objects. Foundation subtraction gives the most complete component information, however it is

incredibly touchy to dynamic scene modifications because of enlightenment changes and unessential occasions.

Analysts are presently committed to building up a vigorous foundation model to anticipate wrongness in movement discovery brought about by scene changes.

The foundation demonstrate is occasionally refreshed utilizing a mix of pixel-and article based strategies. Foundation subtraction speed and exactness rely upon the after effect of the foundation extraction calculation. In the event that there is a scene (outline) with no moving item in the picture groupings, it tends to be a foundation outline a pure foundation picture. In any case, in reality, there is barely to get a pure foundation picture. In such frameworks, as in numerous different applications, removing an unadulterated foundation picture from recordings that incorporate moving items is basic The proposed framework contains a few stages:

- Background extraction: utilizing an improved mode calculation to get an unadulterated

Author for correspondence:

Department of Computer Science and Engineering, Nandha Engineering College

foundation.

- Background subtraction: utilizing a fluffy based foundation subtraction calculation, the closer view is isolated from the foundation and structures a frontal area veil.
- Occlusion recognition: utilizing morphological examination, the framework identifies masses that are associated with having more than one in them.
- Segmentation: utilizing a viable division method dependent on an edge field figured straightforwardly from the pictures. Following: we propose a novel human movement recognition calculation that utilizes a fluffy standard put together characterization conspire with respect to moving mass areas. Whatever remains of the paper is sorted out as pursues: Section 2 portrays related works, and Section 3 depicts proposed framework models for article following. Segment 4 indicates Experimental Results. At long last, Section 5 gives the end.

RELATED WORK

Because of its inescapability in different settings, foundation subtraction has been the focal point of much research. Haritaoglu et al utilize a foundation subtraction demonstrate worked from request measurements of foundation esteems amid a preparation period to actualize a factual shading foundation calculation, which utilizes shading chrominance and brilliance mutilation.

The extraordinary foundation subtraction techniques can be characterized following the model utilized out of sight portrayal steps. Basic Background Modeling, Statistical Background Modeling, Background Estimation.

R. Jain and H. Nagles, 1979 displayed the most punctual way to deal with foundation subtraction in the late 1970s, utilizing outline differencing to recognize moving articles. Ensuing methodologies proposed a movement of probabilistic models to deal with vulnerability in foundation appearance. Analysts have as of late introduced some established calculations for foundation extraction, including the mean, middle, stable interim assurance, change discovery and mode calculations. Specialists have likewise utilized some exceptionally perplexing strategies in foundation extraction calculations, including

textural and factual highlights and hereditary calculations .

Scientists have proposed edge-based closer view divisions that utilization shading data or both shading and angle data. The Wallflower calculation intends to take care of numerous issues in foundation upkeep, including fluctuating lighting conditions, by building up a three-level framework: pixel-, district and edge level. All the more as of late, analysts have researched the Scale Invariant Feature Transform (SIFT), as it can create following highlights that are steady crosswise over edges with a specific measure of camera/object perspective variety. This winds up imperative while thinking about a mix of numerous highlights in the acknowledgment and following procedure, and settling on the best highlights to use under various conditions is fundamental.

Regardless of whether locale based strategies are superior to anything edge-based strategy stays obscure. In any case, it is commonly recognized that the edge-based strategies frequently give better limit localisation. Xie et al, built up a stream field dependent on magneto-static associations between the Active Contours and item limits. Vigilant demonstrated that the primary subsidiary of a Gaussian can surmised the ideal locator. By convolving the picture with this channel, the edge identification is proportionate to finding the inclination extent maxima of a Gaussian-smoothed picture in the fitting course.

Identifying and consolidating edges at different goals and scales is another essential issue in edge discovery. The scale-space method presented by Watkin includes creating coarser goals pictures by convolving the first pictures with a Gaussian smoothing portion. Taj et al assess location and following calculation that utilizes a factual foundation model and diagram coordinating. Dark colored et al present a novel technique to assess foundation subtraction and following execution. They coordinate the ground-truth tracks to tracks identified in the video by contrasting the recognized track centroid with a broadened ground truth bouncing box that supports the tracks of extensive articles.

Bashir and Porikli proposed both edge and item based measures to quantitatively examine the execution of article recognition frameworks. They

for the most part contrast the ground truth bouncing box with the test information outline and register the genuine and false discoveries.

SYSTEM ARCHITECTURE

Fig. 1 gives the square chart of the proposed framework for individuals division, following and checking. The primary objective of social order following is following individuals in unconstrained and jumbled situations as they structure gatherings, associate and part from the gathering in nearness

of impediment. The proposed calculation contains two stages: closer view division and following. At closer view division, to streamline the issue, we expect that the camera is stationary and the foundation demonstrate is static. The initial step of the calculation is foundation subtraction, which, in our setup, is performed on a square dimension. For high edge rate groupings, the neighbouring edge subtraction technique is utilized, as the movement change between back to back edges is little. This technique takes out the stationary foundation, leaving just the ideal movement locales.




Fig.1.Proposed Method

BACKGROUND ESTIMATION

The fundamental test of foundation subtraction is assessing a strong scene foundation to deal with enlightenment and static item changes. The foundation estimation calculation makes a reference picture, which speaks to the foundation of the scene see. The foundation picture is key to recognizing moving items and following them and isolates the foundation from the frontal area. We expect that the video grouping is caught in a RGB shading space by a stationary camcorder. The issue with the RGB shading space is its extraordinary affectability to sensor clamor and lighting condition changes. We first proselyte the casing from RGB to HSV shading space.

The foundation estimation must be dynamic, implying that the foundation picture must be refreshed. This is imperative for a decent people tallying calculation. For instance, if the general

population including framework is set in the passageway of one building, some little and moderate changes happen amid the day and can parasite the general population checking calculation (all the more especially, the foundation distinction calculation). Truth be told, the daylight force changes for the duration of the day, or a few items could be expelled from or added to the work scene. In the event that the foundation estimation is never recomputed, the calculation dependably recognizes varieties. Prior to propelling the foundation estimation, the calculation must be sure that there is no movement in the field of the camcorder amid this minute. In the event that it recognizes no movement, the reference picture (foundation picture) is refreshed; if there is movement, the foundation picture isn't refreshed and endeavours to be refreshed in the following foundation estimation.

We propose a novel foundation extraction calculation dependent on an improved mode algorithm to get the static foundation locales. Utilizing these methodologies tries to acquire a spotless static background reference picture and apply it to foundation subtraction. For high edge rate arrangements, it utilizes the neighbouring casing subtraction strategy, as the movement change between continuous edges is little. This technique kills the stationary foundation, leaving just the ideal movement locales. In certain video frameworks, the obtaining procedure might be powerless to sporadic changes in brightening, reflection, and clamor.

BACKGROUND SUBTRACTION

In an experimentation system, a typical primer advance in any movement based vision application is acquiring picture outlines from a stationary or moving camera or from various cameras. Subsequent to procuring picture outlines, picture division can be performed utilizing foundation subtraction, contingent upon the casing rate of the video arrangements. In the wake of finishing the foundation estimation, the calculation isolates the frontal area and foundation.

The foundation subtraction picture is a dark scale picture, so it must be changed into a double picture to make the fragmented picture (i.e., closer view and foundation partition). To change a dark scale picture into a parallel picture, an edge must meddle. All pixel esteems littler than this limit contain the scene's experience. This disposes of numerous noisy pixels, which regularly have close qualities, and wipes out a few pixels that speak to the shadows made by the moving articles. Truth be told, in a dim scale picture, an item's shadow of an article, more often than not, does not change the component (shading) of the pixel. This shadow, out of sight subtraction, along these lines has a little esteem.

Proposed logic

In the proposed versatile foundation demonstrating and order conspire, we use picture information from the past edges to figure the joint picture circulation to fabricate a foundation show. In view of these two highlights and the foundation

display, we order the picture obstruct as forefront or foundation. On the off chance that another item is brought away from plain sight or a foundation object is moved before the foundation is refreshed, this article is delegated a closer view object and turns out to be a piece of the outline.

The primary commitment of this paper is a system to isolate moving items. Segregating objects from the versatile foundation is a testing errand on account of the absence of robotized thinking about what is or isn't an objective item, as prove in a video grouping.

For this situation, we could utilize complex item acknowledgment and distinguishing proof calculations. Be that as it may, these calculations are frequently computationally serious and not hearty in a dynamic domain. Our plan depends on a fluffy rationale induction framework, which combines numerous data sources together for basic leadership. Assume we are dealing with edge n , and the article in casing $n - 1$ has been accurately separated. Give the forefront a chance to picture locale in casing n be O_n , which may contain the human body and moving items. Our fluffy rationale deduction framework depends on the accompanying perceptions:

In the event that a picture hinder in O_n belongs to the article, it ought to have a high plausibility of finding a decent match in O_{n-1} . We utilize the whole of supreme distinction (SAD) to quantify the coordinating goodness..

- If numerous squares in its neighbourhood have great matches in O_{n-1} , it is profoundly conceivable that this square likewise has a place with the article.
- If this square is a long way from the anticipated position of the item centroid, depicted in Section 4, the likelihood that this square has a place with the article is low. In light of these perceptions, we separate the accompanying element factors from each square in O_n .
- SAD in movement coordinating. For each square in O_n , we locate its best match in casing $n - 1$.
- The SAD between this square and its best match structure the main component variable. The separation between the new square and the anticipated article centroid.

As indicated by the above guidelines, if an item is perceived as closer view, utilizing the fluffy

deduction framework to disengage moving items dissolves the article due to misclassification. We propose settling fluffy foundation subtraction in the wake of passing morphological activities and neighbourhood data to the picture to fix these missing parts. Morphological tasks are performed on the movement picture. The middle channel is a nonlinear computerized separating procedure, frequently used to evacuate commotion. Such commotion decrease is an average pre-preparing venture to improve the outcomes, after which the middle channel can kill the impact of information clamour esteems with incredibly huge extents. It additionally expels movement at limits. Pixels in the movement district situated along the limit are killed to stay away from any uncertainty of the locale having a place with a moving item. We would thus be able to choose that there is no moving article in the scene. This item can be treated as an ideal article for foundation subtraction. Let be the dim dimensions at pixel directions of the reference foundation picture and the scene picture at casing. This calculation depends on picture differencing methods. It is scientifically spoken to utilizing the accompanying condition: N is the number of pixels in the image used as a scaling factor, $I(t_i)$ is the image I at time i , $I(t_j)$ is the image I at time j and $D(t)$ is the normalised sum of the absolute difference for that time. In an ideal case, when there is no motion, and $D(t)$. However, noise is always presented in images, and a better image model in the absence of motion is, where $n(p)$ is a noise signal.

The esteem $D(t)$, which speaks to the standardized total of the supreme contrast, can be a reference to be contrasted and a limit esteem. To decide the participation elements of these component factors, a lot of enrollment capacities were characterized from these dispersions. The accompanying three guidelines are utilized in our fluffy rationale surmising framework and are delineated in a MATLAB execution.

We design a proposed interference system with the following parameters, using the following proposed rules:

Rule 1: If SAD is medium AND Neighbourhood is small, THEN Object is low

Rule 2: If SAD is high AND Neighbourhood is small AND, THEN Object is high Rule 3: If SAD is

high AND Neighbourhood is high AND, THEN Object s high As indicated by the above principles, if an article is perceived as closer view, we see that utilizing the fluffy surmising framework to disengage moving items dissolves the article because of misclassification.

Tracking

Subsequent to performing division, another picture preparing must be propelled in the parallel picture. To follow objects, the initial step is recognizing all items on the scene and computing their highlights. This procedure is known as a Blob Analysis. It comprises of dissecting the twofold picture, finding the masses present and figuring measurements for every one. The mass highlights commonly determined incorporate the zone (number of pixels that make the mass), edge, area and mass shape. Following calculations plan to reproduce the directions of moving articles inside a scene. The most straightforward following methodologies depend on the abuse of the spatio-worldly progression in the movement of physical items and can be successful when the objects of intrigue are very much isolated and constantly noticeable in the scene. Sadly, in some certifiable settings, the spatio-worldly congruity supposition, however by and large legitimate, is frequently damaged.

We present a calculation that thinks about impediments (two items converge to frame a one of a kind mass) and parts (one article parts into a few parts). Tracking objects in a video-succession can be depicted as pursues. In the event that two casings are in progression, it is profoundly likely that objects recognized in the primary edge compare to objects distinguished in the second edge. Following is the recognizable proof of this correspondence. Relating articles can be pretty much interpreted, and the measure of interpretation relies upon both item speed and edge rate. We can likewise have objects showing up in just a single of the two edges since they enter or leave the scene; moreover, we can have objects that cooperate with one another, shaping a one of a kind article. We present an answer for the following issue, in light of the histogram-based shading model that handles impediments and parts. The difficulties related with individuals following

can be brought about by individuals' comparability fit as a fiddle, shading, size or impediment by other individuals or foundation parts.

Occlusion Detection

Impediment identification is basic for strong and solid vision-based frameworks. Since individuals show up in different structures, we can't utilize any individuals shape models. Since vehicles move arbitrarily, impediments and mess circumstances happen in a muddled way. In such circumstances, confounded vehicles can't be divided by a strategy that utilizes form models. The most powerful technique utilized for this reason must not require any data other than the pictures themselves, despite the fact that this strategy requires some sort of picture division. Dividing pictures with pixel measures is troublesome. Foundation subtraction results in a closer view veil, which is a twofold picture that demonstrates the presence of forefront objects. Masses are detached gatherings of bits that are associated with one another, and masses are developed utilizing the associated part examination. While a few masses contain single articles, a few masses contain more than one item.

B.RGB to HSV Colour Space Conversion

Shading vision can be handled utilizing RGB or HSV shading space. RGB shading space depicts hues by the measure of red, green, and blue present. HSV shading space portrays hues by their tint, immersion, and esteem. In circumstances where shading depiction assumes an indispensable job, the HSV shading model is frequently favored over the RGB display. RGB characterizes shading as a blend of essential hues, while HSV depicts shading utilizing progressively commonplace correlations, including shading, liveliness and splendor. The shading spaces that are ordinarily utilized in video following and reconnaissance are YCbCr and HSV.

HSV (M) restores a M-by-3 network containing a HSV shading map. HSV, independent from anyone else, is indistinguishable length from the

present figure's shading map. The hues start with red, go through yellow, green, cyan, blue, fuchsia, and come back to red. The guide is especially helpful for showing occasional capacities. After completing the colour space conversion for the current and background frames, coefficients are then rounded and bit xor mutually.

Proposed Classification

In the last stage, we propose a fluffy guideline based order way to deal with arrange the removed real mass. The learning based utilized here takes care of the issue of correspondence between applicant locales to evacuate equivocalness, make sensible development extrapolations and foresee display setups utilizing a standard set. This standard set inclines toward areas with bigger separations and forestalls following from finding close to the head, keeps the head to be distinguished.

Amid markr district following, mistakes regularly happen because of blemished following an outcome, i.e., a locale vanish or gets impeded or the lighting level in the watched condition changes. Refreshing the model amid following, extrapolating developments if there should arise an occurrence of impediments or information misfortune, and deciding the situation in the following casing are along these lines important. On the off chance that the picture handling gives information, another application is overhead following of people and gatherings. Here, movement identification, luminance-level division, and mass examination are utilized with the standard based methodology depicted previously. The procedure is as per the following: after the framework recognizes huge movement over somewhere around five edges, it refreshes its inner parameters for item luminance levels. This guarantees the items can in any case be followed.

A fluffy rationale surmising framework is set up to save the human body in casing n while segregating obstructs that compare to non-human antiquities.




Fig 3. Silhouette of the user shown with Search regions

In the proposed technique, we foresee the jumping box of the human body in casing $n+1$ from the measurements of past edges. Our fluffy rationale deduction framework depends on the accompanying perceptions.

- Each and each outline is distinguished
- A bouncing box is determined for each person.
- A individual entering the engaged screen is taken as an article and continues with an exceptional character number until he leaves the edge.
- Continuous observing of the width and stature of the outline.
- Counting starts when another extraordinary identifier number enters the casing.
- Counting memory of the remarkable recognize number is resized and fluffy is handled.
- Input is the width and stature of outline the jumping boxes.

Our proposed logic uses the following six rules, illustrated in Figure 3. The proposed rule is based on three input variables (X , Y , and Z) and one output variable *Count*.

- If (X is CONSTANT) and (Y is CONSTANT) and (Z is FALSE) then (*COUNT* is ONE)
- If (X is CONSTANT) and (Y is CONSTANT) and (Z is FALSE) then (*COUNT* is ONE) If (X is VARYING) and (Y is VARYING) and (Z is TRUE) then (*COUNT* is TWO)
- If (X is VARYING) and (Y is CONSTANT) and (Z is FALSE) then (*COUNT* is ONE)
- If (X is CONSTANT) and (Y is VARYING) and (Z is FALSE) then (*COUNT* is ONE)
- If (X is VARYING) and (Y is CONSTANT) and (Z is TRUE) then (*COUNT* is TWO)
- If (X is CONSTANT) and (Y is VARYING) and (Z is TRUE) then (*COUNT* is TWO), Where X = width, Y = height, and Z = holes.

For approval, we tried the total framework in online human following trials. No dataset is accessible for testing the total following framework due to its dynamic nature. We recorded all analyses to physically separate their ground-truth for execution assessment. MATLAB was utilized as the execution instrument.

For estimating exactness, we embraced diverse measurements: Precision, Recall, and Similarity. Review, additionally called discovery rate, gives the percent of distinguished genuine positives contrasted with the absolute number of genuine encouraging points in the ground truth.

Where tp is the all out number of genuine positives, FN is the all out number of false negatives, and $(tp + fn)$ demonstrates the complete number of things present in the ground truth. On the off chance that the ground truth is given as a parallel discovery, genuine positives (resp. false negatives) are expected as evident positive (resp. false negative) pixels of a solitary picture, and Recall goes about as a pixel-based measure. On the off chance that the ground truth is given as data on the number and highlights of moving articles in an arrangement (with respect to successions having a place with the EC Funded CAVIAR Project, IST 2001), genuine positives (false negatives) are planned as obvious positive (false negative) questions in the entire grouping. Review alone isn't sufficient to analyze distinctive techniques and is commonly utilized related to Precision, likewise called positive expectation, which gives the level of recognized genuine positives contrasted with the all out number of things identified

EXPERIMENT AND ANALYSIS

Data acquisition and ground truth

To evaluate the performance of the proposed algorithm, zenithal cameras mounted 3 m above the ground generated indoor colour video sequences. The videos were captured in an office (640 × 480 pixels, 1635 frames, fluorescent light) and in a corridor (320 × 240 pixels, 1500 frames, daylight). We compared the proposed algorithm with the recently published method for people counting by

Borislav Antic. Table 2 presents the results of this comparison

Here, fp is the all out number of false positives, (tp + fp) shows the all out number of recognized things, and contemplations undifferentiated from those detailed for Recall should be made to clear up the pixel-or casing based methodology of the received measurement. Utilizing the previously mentioned measurements, a technique is viewed as great on the off chance that it achieves high Recall values without giving up Precision.




Fig 4 Membership function of 6 rules of the proposed logic inference system

RESULTS

Table 1 demonstrates the quantity of items in the video succession in each casing. We execute the fluffy based guideline for the occulted edge. In view of the precise human body position expectation, the calculation utilizes a vast fleeting refresh window measure unit in its edges for picture obstructs inside the bouncing box while utilizing a generally little size for those outside the jumping box. The experiments demonstrate the most regular cooperation designs saw that in the past prompted following mistakes. The fluffy based framework can resolve these cases and


ceaselessly track the client's body. We can just analyze the execution of the two techniques by expressing that the improved one gives results, though the other did not create palatable outcomes. The second situation demonstrated an expansion in following unwavering quality in the wake of applying the fluffy technique with a standard set adjusted to the particular lighting conditions. The disappointment rate for basic cases was lower than in customary following. By looking at the two following strategies, creating numbers that measure the issues we needed to comprehend is troublesome.

Table 1: Number of people appearing in each frame

F1	F2	F3	F4	F5	F6	F7	F8	F9	F10	F11	F12	F13	F14	Total
1	2	0	2	1	0	2	0	2	2	1	3	2	2	20

Table 2. Comparison of methods for people counting

	Ground Truth	Proposed
Precision	1.00	1.00
Recall	1.00	0.97

**Fig. 5 Results of people appearing in each frame**

CONCLUSION

This paper shows a novel technique for individuals division, following and tallying. We proposed a fluffy based methodology for consolidating a few heuristics in picture handling applications. The proposed technique utilizes a fluffy induction framework. The calculation utilizes foundation subtraction and depends entirely on the edge stream based frontal area squares to accomplish human division. To deal with article extraction challenges in unique

situations, we melded abnormal state information and low-level highlights and built up a fluffy rationale induction framework for individuals following. Delegate video successions have been utilized to assess the outcome. The proposed individuals checking strategy is straightforward yet productive, and accomplishes on-going execution. The execution of the calculation could be additionally improved with multidimensional unique group task, mean-move following and concurrent following and division.

REFERENCES

- [1]. D. Huang and Tommy W. S. Chow, A people-counting system using a hybrid rbf neural network, *Neural Process. Lett.*, 18(2), 2003, 97–113.
- [2]. J. Bescos, J.M. Menendez, and N. Garcia, Dct-based segmentation applied to a scalable zenithalpeoplecounter, in *Proc. of the IEEE International Conference on Image Processing*, 3, 2003, pp. III–1005–8.
- [3]. P Kovesi., "Image features from phase congruency.", *Videre Journal of Computer Vision Research*, 1(3), 1999, 1-27.
- [4]. Yunqiang, C. & R. Yong, Real Time Object Tracking in Video Sequences, *Signals and Communications Technologies, Interactive Video*, Part II, 2006, 67-88.
- [5]. Nummiaro, K., E. Koller-Meier, & L. Van Gool, A Color-based Particle Filter, *Proc. First International Workshop on Generative-Model-Based Vision*, 2002, 53-60.
- [6]. Rossi, M., & A. Bozzoli, (1994), Tracking and Counting People, *Conf. on Image Processing* Masoud, O. & N. Papanikolopoulos, A Robust Real-time Multi-level Model-based Pedestrian Tracking System, *Proc. ITS merica Seventh Annual Meeting*, 1997, 212-216.
- [7]. S.-C. Cheung and C. Kamath, Robust techniques for background subtraction in urban traffic video, in *Proc.*

- EI-VCIP*, 2004, 881–892.
- [8]. M. Piccardi, Background subtraction techniques: a review, in *Proc.IEEE Int. Conf. Systems, Man,Cybernetics*, 2004, 3099–3104.
- [9]. R. J. Radke, S. Andra, O. Al-Kofahi, and B. Roysam, Image change detection algorithms: a systematic survey, *IEEE Trans. Image Process.*, 14(3), 294307, 2005.
- [10]. P. KaewTraKulPong and R. Bowden: An improved adaptive background mixture model for real-time tracking with shadow detection', Proc. 2nd European Workshop onAdvanced Video Based Surveillance *Systems*, Kingston, U.K., 2001, 149–158.
- [11]. B. Lee, M. Hedley Background Estimation for Video Surveillance, IVCNZ 2002, 315-320.
- [12]. N.McFarlane, C. Schofield, Segmentation and tracking of piglets in images, BMVA 1995, 187-193.
- [13]. J. Zheng, Y. Wang, Extracting Roadway Background Image: A mode based approach, Transportation Research Board, 2006.[15] C Wren, A. Azarbayejani, P finder : Real-Time Tracking of the Human Body, IEEE PAMI, 19(7), 1997, 780 -785.